

7	
_	
	כ
Ī	_
	_


•			В.			•	Lower Concentration	
	•		•			•		
•			•		•	•		
	•		•					_
•	•	•	•	•				Distance (X)
•	•	•	•	•	•	•		- 1
•	•	•	•	•	•	•	ц	
•	•	•	•	•	•	•	ratic	
•	•	•	•	•	•	•	cent	
•	:	•	*	•	•	:	Higher Concentration	

**FIG.** 2












Odorant Vapor Pressure (psi)





**FIG. 7** 

. . . .



00009

50000

40000

30000

20000

10000

-5.00E-01

Time (s)


표 (연 (원


4.50E+00
H2 Reaches 4%
4.00E+00
A2.50E+00
H2 Reaches 0bs. Pt. E
5.00E-01

0.00E+00
H2 Reaches 0bs. Pt. E
5.00E-01

H2 Concentration Profile Vs Time @ Observations C and F

H2 Reaches 4% 27.6 hrs 100000 80000 Time (s) 90009 H2 Reaches Obs. Pt. C 9 min H2 Reaches Obs. Pt. F 30 Seconds H2 Reaches 4% 11.11 hrs 40000 20000 H2 Concentration (%)
1.50E + 00
1.50E + 00 0.00E+00 -4.00E+00 1.00E+00 5.00E-01 4.50E+00 3.50E+00 3.00E+00 -5.00E-01





- 1 Hydrogen production
  2 Supplier hydrogen storage (compressed gas)
  3 Mobile system or stationary system connector
  4 On-board, on-site high pressure hydrogen storage
  5 Fuel cell stack
  6 Odorant 'free' exhaust
  A Odorant adsorbers

FIG. 12




FIG. 13





FIG. 14








FIG. 16




FIG. 17

